



# PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

## Wetrok Antiwax forte

The gentle high-performance industrial cleaner from the Antiwax family - combining a strong performance with increased work safety and greater environmental compatibility





# Wetrok Antiwax forte



**pH value (Concentrate):** 8–9

**Important ingredients:**

Surfactants, Solvents, Soap, Fragrances

**Recommended dosage:**



**Maintenance cleaning**

0.05 – 0.1 l/10 l



**Intermediate cleaning**

0.1 – 0.2 l/10 l



**Deep cleaning**

3–5 l/10 l

**Wax removal**

1 l–3 l/10 l

**METHODS  
finder**



**APPLICATION**

- High-performance deep and industrial cleaner
- For the removal of oil, grease and general industrial soiling
- For cleaning washable and solvent-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, etc.)
- Also suitable for cleaning non-sealed wood floors
- Can also be used for removal of polymer and wax coatings

**PROPERTIES**

- Low lather
- Slightly alkaline
- Scented
- Contains solvents

**GOOD TO KNOW**

- The right choice where a wide range of difficult cleaning jobs must be performed with an increased level of work safety and in a more environment-friendly manner.

**PLEASE NOTE**

- Not suitable for maintenance cleaning of self-shine floor coverings
- Use a maximum concentration of 5% on varnished surfaces or elastomers (synthetic or natural rubber)

**RECOMMENDED APPLICATION METHOD**

**Basic cleaning**

Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Apply the basic cleaning solution to the floor covering, allow it to take effect for 15 minutes without letting it dry out! Wet scrub with a single-brush machine and a suitable pad or brush. Vacuum off the dissolved coating, dirt and remaining cleaning product. Then rinse the floor thoroughly using clean water (up to approx. pH 7).

**Scrub drying in a single work step**

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

**Wet mopping, two-step process**

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out slightly, wet mop the floor covering. Allow the cleaning solution to take effect without letting it dry! Use the rinsed and thoroughly wrung-out mop to remove the dissolved dirt and the remaining cleaning solution.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.