



# PRODUCT DATASHEET

Sanitary cleaning - Maintenance cleaners

## Wetrok Caledor

The non-corrosive sanitary maintenance cleaner removes limescale efficiently, no matter how hard the water





# Wetrok Caledor



**pH value (Concentrate):** 0.5–1.5

**Important ingredients:**

Surfactants, Acids, Solvents, Fragrances,  
Colourant, Corrosion inhibitor

**Recommended dosage:**



**Maintenance cleaning**

0.1–0.2 l/10 l



**Intermediate cleaning**

0.3–0.4 l/10 l



**Foaming by hand (foam bottle)**

1 l/10 l

METHODS  
finder



**APPLICATION**

- For the quick and thorough removal of limescale, even in hard water
- For maintenance cleaning of washable and acid-resistant surfaces (sanitary porcelain, fittings, ceramic tiles, bathrooms, showers, washrooms and WCs, etc.)

**PROPERTIES**

- High-lather
- Highly acidic
- Scented
- Not corrosive towards chrome-plated sanitary fittings
- Dries quickly and without leaving streaks

**GOOD TO KNOW**

- The exterior of sanitary fittings must not be warm when cleaning
- Can be foamed by hand with a dosage of 10%

**PLEASE NOTE**

- Not suitable for acid-sensitive surfaces (limestone, marble, clinker, aluminium, etc.)

**RECOMMENDED APPLICATION METHOD**

**Damp wiping (by hand, using a bucket)**

Soak the cloth with cleaning solution and then wring it out well. Wipe the surface with a damp cloth.

**Damp wiping (manual foaming)**

Apply the cleaning foam in an “X” form on a folded cloth, then damp wipe the surface (using the fold technique).

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.