



PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

Minatol Ergo 8

Ergo 4 has a big brother that can handle complex industrial cleaning tasks





Minatol Ergo 8



pH value (Concentrate): 13–14

Important ingredients:

Surfactants, Solvents, Soap, Fragrances

Recommended dosage:



Maintenance cleaning

0.05 l-0.2 l/10 l



Deep cleaning

0.2 l-1 l/10 l

**METHODS
finder**



APPLICATION

- High-performance deep and industrial cleaner
- For the removal of wax, oil, grease and general industrial soiling
- For the removal of oil and soot from barbecues, wheel rims, chassis and engines
- For cleaning washable and alkali-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, asphalt, etc.)

PROPERTIES

- Low lather
- Highly alkaline
- Contains solvents
- Lightly scented

GOOD TO KNOW

- suitable for the removal of oil and soot from wheel rims, chassis and engines

PLEASE NOTE

- Not suitable for maintenance cleaning of self-shine floor coverings
- Not suitable for linoleum, natural rubber, wooden flooring, or painted or varnished surfaces

RECOMMENDED APPLICATION METHOD

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

Scrub drying in a two-step process

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush (without vacuuming). Leave the cleaning solution to take effect. Observe the contact time! Do not allow to dry out! Follow up with the scrubber-dryer (lower suction nozzle). Scrub-dry the floor covering.

Wet mopping, single work step

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.