



PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

Wetrok EXAL 2000

High-performance cleaner for removing oils, grease, general industrial soiling and wax coatings





Wetrok EXAL 2000



pH value (Concentrate): 10–11

Important ingredients:

Surfactants, Soap, Solvents, Chelating agents, Fragrances, Colourants, Preservatives

Recommended dosage:



Maintenance cleaning

0.1 l/10 l



Intermediate cleaning

0.5–1 l/10 l



Basic cleaning

1 l–3 l/10 l

METHODS
finder



APPLICATION

- For the removal of oil, grease and general industrial soiling
- Suitable for removing protective films (wax coatings)
- For cleaning washable and alkali-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, asphalt, etc.)

PROPERTIES

- Low lather
- Slightly alkaline
- Scented

PLEASE NOTE

- Not suitable for maintenance cleaning of self-shine floor coverings

RECOMMENDED APPLICATION METHOD

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

Wet mopping, single work step

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.