



PRODUCT DATASHEET

Carpet cleaning - Carpet cleaners

Wetrok Fomstop

Anti-foaming agent for spray extraction machines, scrubber-dryers and wet vacuum cleaners





Wetrok Fomstop



pH value (Concentrate): 5–6

Important ingredients:

Surfactants, Silicones, Fatty acid, Preservatives

Recommended dosage:

Normal-lather

1 l/10 l

High-lather

2 l/10 l

METHODS
finder



APPLICATION

- Anti-foaming agent, reduces lathering in spray extraction machines, scrubber-driers and wet vacuum cleaners

PROPERTIES

- Silicone-based
- Unscented
- Solvent-free

PLEASE NOTE

- Observe operating instructions for the respective equipment
- With spray extraction equipment: add mixture to recovery tank
- With scrubber-driers and wet vacuum cleaners: mix directly in the recovery tank

RECOMMENDED APPLICATION METHOD

Use with spray extraction equipment

Pour the product into the defoamer device or fill the waste water tank with water, then add the product at the appropriate dosage. Add the mixture to the dirty water via the injector nozzle and set the injector to the required flow rate.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.