



# PRODUCT DATASHEET

All-purpose cleaning - Surface cleaning

## Wetrok KLP

High-performance cleaner for grease, paint and industrial dirt -  
suitable for spot cleaning - dries quickly and without leaving  
streaks





# Wetrok KLP



**pH value (Concentrate):** 12–13

**Important ingredients:**

Surfactants, Solvents, Dispersing agents

**Recommended dosage:**



**Maintenance cleaning**

0.1 l/10 l



**Intermediate cleaning**

0.1 l-10 l/10 l

METHODS  
finder



**APPLICATION**

- Plastic/laminate/PVC cleaner and high-performance industrial cleaner and stain remover
- For removing oil, grease and general industrial soiling
- Also suitable for removing paint residues
- For cleaning washable, alkali-resistant surfaces and floor coverings (surfaces containing plastic, laminate, PVC, stone, ceramics, stainless steel, high-grade steel, glass)

**PROPERTIES**

- Highly alkaline
- Unscented
- Contains solvents

**GOOD TO KNOW**

- Higher dosages are suitable for spot cleaning
- Dries quickly and without leaving streaks

**PLEASE NOTE**

- Do not use on polymer-coated floors (these may be affected)

**RECOMMENDED APPLICATION METHOD**

**Damp wiping (by hand, using a bucket)**

Soak the cloth with cleaning solution and then wring it out well. Wipe the surface with a damp cloth.

**Wet mopping, single work step**

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.