



# PRODUCT DATASHEET

Protective treatment - Wood treatment oil

## Wetrok Leinol BW

The EMICODE EC1+ certified wood treatment oil for basic care of sanded wooden floors





# Wetrok Leinol BW

## APPLICATION

- for basic care and initial treatment of absorbent and sanded wooden floors, offers optimal and long-lasting protection against water and dirt.
- good for people and the environment - awarded EMICODE EC1 Plus (very low emissions).
- easier finishing than with classic solid wood oils.

## PROPERTIES

- aqueous linseed oil emulsion
- matt to satin finish
- EMICODE EC1 Plus - very low emissions

## GOOD TO KNOW

- use Leinol NW for aftercare or wipe and care.

## PLEASE NOTE

- shake well before use
- textiles that come into contact with the product are at risk of spontaneous combustion when drying

## RECOMMENDED APPLICATION METHOD

### Oil treatment (protective treatment)

The floor must be dry, clean and absorbent. Dry vacuum/mop the floor covering to collect dust. Apply a little oil and allow it to soak in. Spread and work in any excess oil. Drying time (3 days to 1 week). Then use a single-brush machine with a blue pad to equalize the surface.

## STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.



**pH value (Concentrate):** 6–7

### Important ingredients:

Linseed oil, Polymers, Waxes, Surfactants

### Recommended dosage:



**Basic care**

Undiluted

**METHODS**  
finder

