



PRODUCT DATASHEET

Kitchen cleaning - Maintenance cleaners

Wetrok Poxex

High-performance kitchen maintenance cleaner for removing animal and vegetable grease and oils - suitable for machine use





Wetrok Poxlex



pH value (Concentrate): 10–11

Important ingredients:

Surfactants, Soap, Chelating agents, Preservatives

Recommended dosage:



Maintenance cleaning

0.05 – 0.1 l/10 l



Intermediate cleaning

0.2 – 0.4 l/10 l

METHODS
finder



APPLICATION

- High-performance universal cleaner
- Cleaner for removing animal and vegetable grease and oils.
- For cleaning alkali-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, asphalt, etc.)
- For cleaning in food processing areas (canteens, restaurants, industrial and manufacturing plants)

PROPERTIES

- Non-foaming
- Slightly alkaline
- Unscented
- Solvent-free

PLEASE NOTE

- Rinse all work implements as well as the tank and conduit systems of automatic scrubbers with clear water after use

RECOMMENDED APPLICATION METHOD

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

Wet mopping, single work step

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

Wet wiping (by hand)

Wash the dirty surface with cleaning solution. Wet scrub using a suitable hand pad or brush. Use a cloth to remove the dissolved dirt and the remaining cleaning solution. Rinse the cleaned surface with clean, cold water and wipe it dry as needed.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use. Protect against frost.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.