



# PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

## Wetrok Relino

High-performance deep cleaner for linoleum





# Wetrok Relino



**pH value (Concentrate):** 10.5–11.5

**Important ingredients:**

Surfactants, Solvents, Soap, Chelating agents

**Recommended dosage:**



**Intermediate cleaning**

0.2–0.5 l/10 l



**Deep cleaning**

2–5 l/10 l

METHODS  
finder



**APPLICATION**

- High-performance deep cleaner for linoleum
- For removal of polymer and wax coatings
- For cleaning of washable and solvent-resistant floor coverings using a machine (PVC, natural and artificial stone, clinker, linoleum etc.)

**PROPERTIES**

- Low lather
- Slightly alkaline
- Contains solvents
- Unscented

**PLEASE NOTE**

- Not suitable for asphalt or painted surfaces
- Not suitable for acid-sensitive floor coverings

**RECOMMENDED APPLICATION METHOD**

**Basic cleaning**

Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Apply the basic cleaning solution to the floor covering, allow it to take effect for 15 minutes without letting it dry out! Wet scrub with a single-brush machine and a suitable pad or brush. Vacuum off the dissolved coating, dirt and remaining cleaning product. Then rinse the floor thoroughly using clean water (up to approx. pH 7).

**Scrub drying in a single work step**

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.