



PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

Wetrok Remat forte

High-performance deep cleaner for high alkaline cleaning jobs





Wetrok Remat forte



pH value (Concentrate): 13–14

Important ingredients:

Surfactants, Solvents, Base, Soap

Recommended dosage:



Intermediate cleaning

0.1–0.5 l/10 l



Deep cleaning

1–2 l/10 l

Removal of encrustations

2 l / 10 l

METHODS
finder



APPLICATION

- Very powerful deep cleaner for removal of polymer and wax coatings
- Effective removal of encrustations
- For cleaning of washable and alkali-resistant floor coverings using a machine (PVC, natural and artificial stone, clinker, etc.)

PROPERTIES

- Low lather
- Contains solvents
- Highly alkaline
- Unscented

PLEASE NOTE

- Dosage max. 20% for polished artificial stone, epoxy and PU floor coverings
- Not suitable for linoleum, natural rubber, wooden flooring, asphalt, painted surfaces
- Rinse work implements with water after using

RECOMMENDED APPLICATION METHOD

Basic cleaning

Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Apply the basic cleaning solution to the floor covering, allow it to take effect for 15 minutes without letting it dry out! Wet scrub with a single-brush machine and a suitable pad or brush. Vacuum off the dissolved coating, dirt and remaining cleaning product. Then rinse the floor thoroughly using clean water (up to approx. pH 7).

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.