



# PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

## Wetrok Remat

The deep cleaner for all alkali-resistant floor coverings





# Wetrok Remat

## APPLICATION

- High-performance deep cleaner
- For removal of polymer and wax coatings
- For cleaning of washable and alkali-resistant floor coverings using a machine (PVC, natural and artificial stone, clinker, etc.)

## PROPERTIES

- Low lather
- Contains solvents
- Highly alkaline
- Lightly scented

## PLEASE NOTE

- Not suitable for linoleum, natural rubber, wooden flooring, asphalt, painted surfaces

## RECOMMENDED APPLICATION METHOD

### Basic cleaning

Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Apply the basic cleaning solution to the floor covering, allow it to take effect for 15 minutes without letting it dry out! Wet scrub with a single-brush machine and a suitable pad or brush. Vacuum off the dissolved coating, dirt and remaining cleaning product. Then rinse the floor thoroughly using clean water (up to approx. pH 7).

### Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

## STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.



**pH value (Concentrate):** 12.5–13.5

### Important ingredients:

Surfactants, Solvents, Soap, Fragrances

### Recommended dosage:



#### Intermediate cleaning

0.1–0.5 l/10 l



#### Deep cleaning

1–2 l/10 l

#### Removal of encrustations

2 l/10 l

METHODS  
finder

