



PRODUCT DATASHEET

Floor cleaning - Maintenance cleaners

Wetrok Reshine

Very powerful and versatile maintenance cleaner certified according to DIN 18032 - strong, quick wetting for streak-free results, protects the floor's shine





Wetrok Reshine



pH value (Concentrate): 9–10

Important ingredients:

Surfactants, Soap, Solvents, Chelating agents, Fragrances, Preservatives

Recommended dosage:



Maintenance cleaning

0.1–0.2 l/10 l



Intermediate cleaning

0.2 l–0.5 l/10 l

METHODS
finder



APPLICATION

- For maintenance cleaning of washable and alkali-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, asphalt, linoleum, natural rubber, etc.)
- Very high-performance, versatile maintenance cleaner

PROPERTIES

- Low lather
- Slightly alkaline
- Lightly scented
- Protects the floor's shine
- Conforms to DIN 18032

GOOD TO KNOW

- Reduces microcracks and ensures a uniform appearance

RECOMMENDED APPLICATION METHOD

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

Wet mopping, single work step

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.