



PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

Wetrok Rewit 2000

The specialist for asphalt surfaces





Wetrok Rewit 2000



pH value (Concentrate): 10.5–11.5

Important ingredients:

Surfactants, Soap, Solvents, Chelating agents, Fragrances

Recommended dosage:



Maintenance cleaning

0.05 – 0.1 l/10 l



Intermediate cleaning

0.2–0.5 l/10 l



Deep cleaning

1–2 l/10 l

METHODS
finder



APPLICATION

- High-performance deep cleaner
- For removal of polymer and wax coatings
- For cleaning washable and alkali-resistant floor coverings (PVC, natural and artificial stone, clinker, etc.)
- Suitable for cleaning asphalt

PROPERTIES

- Low lather
- Slightly alkaline
- Contains solvents

PLEASE NOTE

- Dosage max. 5 % for linoleum
- Not suitable for maintenance cleaning of floor coverings treated with self-shining dispersion
- Not suitable for acid-sensitive floor coverings

RECOMMENDED APPLICATION METHOD

Basic cleaning

Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Apply the basic cleaning solution to the floor covering, allow it to take effect for 15 minutes without letting it dry out! Wet scrub with a single-brush machine and a suitable pad or brush. Vacuum off the dissolved coating, dirt and remaining cleaning product. Then rinse the floor thoroughly using clean water (up to approx. pH 7).

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

Wet mopping, single work step

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.