



# PRODUCT DATASHEET

Protective treatment - Coatings

## Wetrok Stoner

The specially developed protective treatment for slightly porous natural and artificial stone floor coverings





# Wetrok Stoner



**pH value (Concentrate):** 8–9

**Important ingredients:**

Polymers, Waxes, Alkali-soluble resins,  
Solvents, Surfactants, Preservatives

**Recommended dosage:**



**Spray cleaning**  
3–5 l/10 l



**Protective treatment**  
Undiluted

METHODS  
finder



**APPLICATION**

- The protective treatment specially designed for stone
- Specially developed for slightly porous natural and artificial stone floor coverings
- For treating hard and elastic floor coverings (PVC, linoleum, natural and artificial stone, etc.)

**PROPERTIES**

- Polymer/wax-based
- High-shine
- Water vapour diffusion guaranteed
- Forms a polishable, water-resistant protective film

**PLEASE NOTE**

- Shake well before use
- Not suitable for water and damp-sensitive floor coverings (e.g. anhydrite), for outdoor areas and wet zones
- Treat porous floor coverings with Porosol before use
- Apply at a temperature of 15-25°C and 30-70% relative humidity
- Before each use, make sure that the floor covering is pH-neutral

**RECOMMENDED APPLICATION METHOD**

**Coating (protective treatment)**

The floor covering must be clean, free of any earlier treatment and completely dry (<3% residual moisture, CM method). Dry vacuum/mop the floor covering to collect dust. Apply the protective coating in sections in 2 to 3 thin coatings. Allow the floor to dry well between coats (at least 60 minutes). Where required, polish with a polishing pad once fully dry (after 2 to 3 days).

**Spray cleaning**

Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Spray on a small amount of the cleaner and work it in immediately in a circular motion, using with a single-brush machine and red pad. Reverse or replace pads when dirty or worn out. Polish dry if needed.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use. Protect against frost.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.