



# PRODUCT DATASHEET

Sanitary cleaning - Maintenance cleaners

## Wetrok wetco san

Certified environmentally friendly sanitary maintenance cleaner for daily removal of limescale - ideal for low to moderate water hardness





# Wetrok wetco san



**pH value (Concentrate):** 0.5–1.5

**Important ingredients:**

Surfactants, Acid, Colourant

**Recommended dosage:**



**Maintenance cleaning**

0.1 l/10 l



**Foaming by hand (foam bottle)**

1.0 l/10 l

METHODS  
finder



**APPLICATION**

- Sanitary maintenance cleaner for removing limescale
- For maintenance cleaning of washable surfaces and equipment (sanitary porcelain, fittings, ceramic tiles, bathrooms, showers, washrooms and WCs, etc.).
- Certified environmentally friendly maintenance cleaner (Nordic Ecolabel)

**PROPERTIES**

- High-lather
- Highly acidic
- Unscented

**GOOD TO KNOW**

- The exterior of sanitary fittings must not be warm when cleaning
- Ideal for low to moderate water hardness

**PLEASE NOTE**

- Not suitable for acid-sensitive surfaces (limestone, marble, clinker, aluminium, etc.)

**RECOMMENDED APPLICATION METHOD**

**Damp wiping (manual foaming)**

Apply the cleaning foam in an "X" form on a folded cloth, then damp wipe the surface (use the fold technique). Rinse the cleaned surface with clean, cold water and wipe it dry as needed.

**Wet wiping (by hand)**

Wash the dirty surface with cleaning solution. Wet scrub using a suitable hand pad or brush. Use a cloth to remove the dissolved dirt and the remaining cleaning solution. Rinse the cleaned surface with clean, cold water and wipe it dry as needed.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.