




Product data sheet Mepol HM

V 04 / 31.12.2020



Wetrok Mepol HM

Coating



Recommended dosage:



Protective treatment
Undiluted

Benefits:

Satin-finish protective treatment.

Application:

For treating hard and elastic floor coverings (PVC, linoleum, natural and cast stone, etc.).

Please note:

Shake well before use!

Not suitable for water and damp-sensitive floor coverings (for e.g. anhydrite), as well as outdoor areas or wet zones.

Treat porous floor coverings with Wetrok Porosol before use.

Properties:


Polymer/wax-based

Matt to satin finish

Water vapour diffusion guaranteed

Forms a water-resistant protective film

pH value of concentrate:



Important ingredients:

Polymers, wax, solvents, surfactants, preservatives

Storage/shelf life:

Store in original container in a cool, well-ventilated place.

Protect from frost. Keep container closed when not in use.

Shelf life (unopened): 24 months.

Recommended application methods:

Protective treatment

The floor must be free of any earlier treatment and completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply the protective coating in sections in 2 to 3 thin coatings.

Allow at least 60 min. drying time between coatings.

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.