




Product data sheet Rewit 2000

V 02 / 06.07.2016



Wetrok Rewit 2000

Basic and industrial cleaners



Recommended dosage (in cold water):



Maintenance cleaning
0.05 l – 0.1 l / 10 l



Intermediate cleaning
0.2 l – 0.5 l / 10 l



Basic cleaning
1 l – 2 l / 10 l

Benefits:

High-performance basic cleaner.
For removal of polymer and wax coatings.
Good asphalt cleaner.

Application:

For mechanical cleaning of washable and alkali-resistant floor coverings (PVC, natural and cast stone, clinker, etc.).


Please note:

Use Wetrok Rewit 2000 in a maximum 5% solution on linoleum.

Properties:

Low lather
Slightly alkaline
Contains solvents

pH value of concentrate:



Important ingredients:

Surfactants, soap, solvents, chelating agent, fragrance

Storage/shelf life:

Store in original container in a cool, well-ventilated place.
Protect from frost. Keep container closed when not in use.
Shelf life (unopened): 24 months.

Recommended application methods:

Scrub drying

Fill up the fresh water tank with the cleaning solution. Remove any loose dirt, and dust mop or dry vacuum the floor. Scrub dry the floor covering thoroughly with a scrubber-drier and suitable pad or brush.

Basic cleaning

Remove any loose dirt, and dust mop or dry vacuum the floor. Apply the basic cleaning solution to the surface, leave to act for 15 minutes without allowing to dry out! Wet scrub with a single-brush machine / automatic scrubber and a suitable pad or brush. Leave the solution to act for 10 minutes. Do not allow to dry out! Vacuum up the dissolved coating or soiling. Then rinse the floor covering well with clean water (up to approx. pH 7).