

Foam cleaning Industrial foaming, low pressure cleaning



	Description	
Definition / objective	Removing loose and stubborn dirt from the surfaces using the foamed cleaning product solution from the foaming device. Suitable for water-resistant surfaces (walls and furniture).	
Preparatory work		Select suitable products to match the surface to be cleaned (type / square metres) and the type of soiling.
		Check, equip and ready the device and all accessories in compliance with the instructions for use.
		Fill the foam cleaning product in accordance with the dosing instructions into the container on the foaming device or connect the container directly to the low-pressure unit.
		Put up the warning sign.
		Pre-clean the surface with plenty of water and remove any loose dirt. Rinse from the bottom up and finish by rinsing the floor.
Main task	A	Apply the cleaning foam to the surface to be cleaned, working from the bottom up in slightly overlapping passes.
		Allow the cleaning foam to take effect as needed, but don't let it dry.
		Remove highly stubborn soiling with the soft brush or the non-abrasive pad.
		Rinse the surface to be cleaned with plenty of clear water, working from the top down in overlapping passes.
		As needed: Dry the fittings, the walls and the floor.
		Perform a visual check.
Final steps	Remove the warning sign once the floor covering is dry.	
	Dispose of any waste.	
	Clean the cleaning equipment and replace as needed.	
Comments	 Wear the personal protective equipment (PPE) required by company regulations, safety data sheets and / or instructions for use. Always check in advance which product meets your requirements (see Wetrok Cleaning & Care Instructions). Wetrok AG accepts no liability for damage caused by improper use or incorrect product selection. 	