



# PRODUCT DATASHEET

Sanitary cleaning - Basic cleaners

## Wetrok Calexan forte

Highly acidic basic cleaner for sanitary areas. Protects sanitary fittings against corrosion Removes limescale in all water hardness conditions





# Wetrok Calexan forte



**pH value (Concentrate):** 0–1

**Important ingredients:**

Surfactants, Acid, Colourant, Corrosion inhibitor

**Recommended dosage:**



**Intermediate cleaning**

0.1–0.5 l/10 l



**Deep cleaning**

0.5–2 l/10 l



**Foaming by hand (foam bottle)**

2 l/10 l



**For removing cement residue**

2–4 l/10 l

METHODS  
finder



**APPLICATION**

- Efficiently removes limescale in all water hardness conditions
- For cleaning washable and acid-resistant surfaces (sanitary porcelain, fittings, ceramic tiles, bathrooms, showers, washrooms and WCs, etc.)
- Also suitable for removing cement residues

**PROPERTIES**

- Highly acidic
- Unscented
- High-lather
- Not corrosive towards chrome-plated sanitary fittings

**GOOD TO KNOW**

- The exterior of sanitary fittings must not be warm when cleaning
- Allow the product to take effect without letting it dry

**PLEASE NOTE**

- Not suitable for acid-sensitive surfaces (limestone, marble, clinker, aluminium, etc.)
- Moisten non acid-resistant grout material with water before use

**RECOMMENDED APPLICATION METHOD**

**Descaling (by hand, with foam)**

Wet the fitting and surface with plenty of water. Then apply the cleaning foam and allow it to take effect. Do not allow to dry out! Rinse with clean, cold water, then wipe with a clean, dry cloth.

**Wet wiping (by hand)**

Wash the dirty surface with cleaning solution. Wet scrub using a suitable hand pad or brush. Use a cloth to remove the dissolved dirt and the remaining cleaning solution. Rinse the cleaned surface with clean, cold water and wipe it dry as needed.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.