PRODUCT DATASHEET

Sanitary cleaning - Basic cleaners



High-performance basic sanitary cleaner for removing limescale and cement residues - for moderately hard water





Wetrok Calexan





pH value (Concentrate): 0.5-1.5

Important ingredients: Surfactants, Acids, Fragrances, Colourant

Recommended dosage:



Maintenance cleaning 0.1-0.5 1/10 1



1 I–3 I/10 I

Foaming by hand (foam bottle)

2 1/10



For removing cement residues Undiluted

METHODS finder



APPLICATION

- For removing limescale and cement residues
- For descaling and cleaning washable and acid-resistant surfaces and equipment (sanitary porcelain, fittings, ceramic tiles, bathrooms, showers, washrooms and WCs, etc.)

PROPERTIES

- High-lather
- Highly acidic
- Lightly scented

GOOD TO KNOW

- Can also be used as maintenance cleaner
- The exterior of sanitary fittings must not be warm when cleaning
- Suitable for quickly removing cement residues on construction sites

PLEASE NOTE

- Not suitable for acid-sensitive surfaces (limestone, marble, clinker, aluminium, etc.)
- Moisten non acid-resistant grout material with water before use

RECOMMENDED APPLICATION METHOD

Damp wiping (manual foaming)

Apply the cleaning foam in an "X" form on a folded cloth, then damp wipe the surface (use the fold technique). Rinse the cleaned surface with clean, cold water and wipe it dry as needed.

Wet wiping (by hand)

Wash the dirty surface with cleaning solution. Wet scrub using a suitable hand pad or brush. Use a cloth to remove the dissolved dirt and the remaining cleaning solution. Rinse the cleaned surface with clean, cold water and wipe it dry as needed.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.

