



PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

Minatol Ergo 22

Gear up to tackle the most challenging industrial cleaning tasks





Minatol Ergo 22



pH value (Concentrate): 10–11

Important ingredients:

Surfactants, Solvents, Soap, Fragrances

Recommended dosage:



Maintenance cleaning

0.05 – 0.1 l/10 l



Intermediate cleaning

0.2 l – 1 l/10 l



Deep cleaning

0.5 – 2 l/10 l

**METHODS
finder**



APPLICATION

- High-performance deep cleaner
- For removing oily and greasy soiling
- For cleaning washable alkali- and solvent-resistant floor coverings and surfaces (PVC, natural and artificial stone, clinker, etc.)
- For the removal of oil and soot from engines

PROPERTIES

- Low lather
- Slightly alkaline
- Contains solvents
- Scented

PLEASE NOTE

- Not suitable for maintenance cleaning of self-shine floor coverings

RECOMMENDED APPLICATION METHOD

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

Scrub drying in a two-step process

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush (without vacuuming). Leave the cleaning solution to take effect. Observe the contact time! Do not allow to dry out! Follow up with the scrubber-dryer (lower suction nozzle). Scrub-dry the floor covering.

Wet mopping, two-step process

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out slightly, wet mop the floor covering. Allow the cleaning solution to take effect without letting it dry! Use the rinsed and thoroughly wrung-out mop to remove the dissolved dirt and the remaining cleaning solution.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.