



PRODUCT DATASHEET

Floor cleaning - Industrial and deep cleaners

Minatol Ergo 4

The industrial cleaner for all common cleaning tasks





Minatol Ergo 4



pH value (Concentrate): 13–14

Important ingredients:

Surfactants, Solvents, Chelating agents, Soap, Fragrances

Recommended dosage:



Deep cleaning
0.5–0.8 l/10 l

**METHODS
finder**



APPLICATION

- high-performance deep and industrial cleaner
- for the removal of heavy oily and greasy soiling
- for cleaning water- and alkali-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, asphalt, etc.)

PROPERTIES

- Low lather
- Highly alkaline
- Contains solvents
- Lightly scented

PLEASE NOTE

- Not suitable for alkali-sensitive floor coverings and surfaces (linoleum, natural rubber, aluminium, enamel, etc.)

RECOMMENDED APPLICATION METHOD

Scrub drying in a single work step

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

Scrub drying in a two-step process

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush (without vacuuming). Leave the cleaning solution to take effect. Observe the contact time! Do not allow to dry out! Follow up with the scrubber-dryer (lower suction nozzle). Scrub-dry the floor covering.

Wet mopping, two-step process

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out slightly, wet mop the floor covering. Allow the cleaning solution to take effect without letting it dry! Use the rinsed and thoroughly wrung-out mop to remove the dissolved dirt and the remaining cleaning solution.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.