



PRODUCT DATASHEET

Protective treatment - Impregnation

Wetrok Imprasol

The impregnating agent for porous natural and artificial stone coverings





Wetrok Imprasol



pH value (Concentrate): -

Important ingredients:

Hydrophobic compounds, Preservatives

Recommended dosage:



Sealing

Undiluted

**METHODS
finder**



APPLICATION

- For impregnating natural and artificial stone coverings
- For treating porous, highly absorbent floor coverings (clay tiles, sandstone, marble, clinker, slate, etc.)

PROPERTIES

- Improves cleanability
- Colourless/transparent
- Helps to keep soiling on the surface
- Difficult to remove

GOOD TO KNOW

- Try in an inconspicuous spot before use, as the product may cause slight discolouration of surfaces
- Consumption: 20 - 50 g/m²
- Allow at least 24 hours drying time

PLEASE NOTE

- Shake well before use
- Not suitable for water and damp-sensitive floor coverings (e.g. anhydrite), for outdoor areas and wet zones
- Apply at a temperature of 15-25 °C and 30-70 % relative humidity

RECOMMENDED APPLICATION METHOD

Impregnation

The floor covering must be absorbent and completely dry (<3% residual moisture). Dry vacuum/mop the floor covering to collect dust.

Slightly absorbent floor coverings: Apply the product to the floor covering in sections, using the spray method. Use a single-brush machine and red pad to work it in uniformly until the surface is free of any excess product.

Highly absorbent floor coverings: Apply the product on the entire surface, using an application tool or mop over the entire surface. The product must soak in.

Wipe off excess product. Leave the floor covering to dry out completely (at least 24h). Check the waterproofing effect and repeat impregnation if necessary.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use. Protect against frost.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.