



PRODUCT DATASHEET

All-purpose cleaning - Surface cleaning

Wetrok KLP

High-performance cleaner for grease, paint and industrial dirt -
suitable for spot cleaning - dries quickly and without leaving
streaks





Wetrok KLP



pH value (Concentrate): 12–13

Important ingredients:

Surfactants, Solvents, Dispersing agents

Recommended dosage:



Maintenance cleaning

0.1 l/10 l



Intermediate cleaning

0.1 l-10 l/10 l

METHODS
finder



APPLICATION

- Plastic/laminate/PVC cleaner and high-performance industrial cleaner and stain remover
- For removing oil, grease and general industrial soiling
- Also suitable for removing paint residues
- For cleaning washable, alkali-resistant surfaces and floor coverings (surfaces containing plastic, laminate, PVC, stone, ceramics, stainless steel, high-grade steel, glass)

PROPERTIES

- Highly alkaline
- Unscented
- Contains solvents

GOOD TO KNOW

- Higher dosages are suitable for spot cleaning
- Dries quickly and without leaving streaks

PLEASE NOTE

- Do not use on polymer-coated floors (these may be affected)

RECOMMENDED APPLICATION METHOD

Damp wiping (by hand, using a bucket)

Soak the cloth with cleaning solution and then wring it out well. Wipe the surface with a damp cloth.

Wet mopping, single work step

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.