

PRODUCT DATASHEET

**Carpet cleaning - Carpet cleaners** 

# **Wetrok Karpex**

The extra-powerful basic and interval cleaner for synthetic carpets





## **Wetrok Karpex**









pH value (Concentrate): 9.5-10.5

## Important ingredients:

Surfactants, Solvents, Chelating agents, Polymers, Fragrances

## Recommended dosage:



Spray extraction (two-step process)

0.3-1 1/10 1



Spray extraction (single work step)

0.1–0.3 l/10 l



Carpet pad method 0.1–0.3 I/10 I

METHODS finder



## **APPLICATION**

- For high-performance basic/intermediate cleaning of synthetic carpets
- For spray extraction
- · Compatible with the carpet pad method

## **PROPERTIES**

- Non-foaming
- Slightly alkaline
- Lightly scented
- No brighteners

#### PLEASE NOTE

- Not suitable for carpets made of virgin wool/mixed fibres or other alkali-sensitive materials if in doubt use Retex!
- Only designed for carpets with synthetic backings (not harmed by water) and water-resistant adhesives

## RECOMMENDED APPLICATION METHOD

### Carpet pad method

Dry or brush vacuum the textile floor covering. Remove the stains with a suitable cleaning product. Spray the cleaning solution onto the textile floor covering and the carpet pad and clean using circular movements of the single-brush machine. Work in sections. Turn over or replace soiled pads. Then brush the carpet pile with a pile brush and allow the floor covering to dry completely.

## Spray extraction

Dry or brush vacuum the textile floor covering. Pre-treat the stains with a suitable cleaning product.

Single work step: Pour the cleaning solution into the water tank and perform spray extraction on the floor covering in a single work step.

Two-step process: Spray the floor with cleaning solution and leave to act for approx. 10 minutes without letting the floor dry. Perform spray extraction on the floor covering using clean water, until the used water remains clear.

Brush the carpet pile with a pile brush and allow the floor covering to dry completely (at least 24 hours).

## **STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.

