



PRODUCT DATASHEET

Protective treatment - Wood treatment oil

Leinol BW

The EMICODE EC1+ certified wood treatment oil for basic care of sanded wooden floors





Leinol BW

APPLICATION

- for basic care and initial treatment of absorbent and sanded wooden floors, offers optimal and long-lasting protection against water and dirt.
- good for people and the environment - awarded EMICODE EC1 Plus (very low emissions).
- easier finishing than with classic solid wood oils.

PROPERTIES

- aqueous linseed oil emulsion
- matt to satin finish
- EMICODE EC1 Plus - very low emissions

GOOD TO KNOW

- use Leinol NW for aftercare or wipe and care.

PLEASE NOTE

- shake well before use
- textiles that come into contact with the product are at risk of spontaneous combustion when drying

RECOMMENDED APPLICATION METHOD

Oil treatment (protective treatment)

The floor must be dry, clean and absorbent. Dry vacuum/mop the floor covering to collect dust. Apply a little oil and allow it to soak in. Spread and work in any excess oil. Drying time (3 days to 1 week). Then use a single-brush machine with a blue pad to equalize the surface.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrot AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.



pH value (Concentrate): 6–7

Important ingredients:

Linseed oil, Polymers, Waxes, Surfactants

Recommended dosage:



Basic care

Undiluted

METHODS
finder

