



PRODUCT DATASHEET

Protective treatment - Wood treatment oil

Wetrok Leinol NW

The EMICODE EC1+ certified wood treatment oil for aftercare of oiled wooden floors





Wetrok Leinol NW

APPLICATION

- for aftercare of all absorbent and oiled wooden floors, offers optimal and long-lasting protection against water and dirt.
- good for people and the environment - awarded EMICODE EC1 Plus (very low emissions).
- can be used both for aftercare or for wipe and care.

PROPERTIES

- aqueous linseed oil emulsion
- matt to satin finish
- EMICODE EC1 Plus - very low emissions

PLEASE NOTE

- shake well before use
- textiles that come into contact with the product are at risk of spontaneous combustion when drying
- untreated wood floors should first be treated with Leinol BW

RECOMMENDED APPLICATION METHOD

Oil treatment (protective treatment)

The floor must be dry, clean and absorbent. Dry vacuum/mop the floor covering to collect dust. Apply a little oil and allow it to soak in. Spread and work in any excess oil. Drying time (3 days to 1 week). Then use a single-brush machine with a blue pad to equalize the surface.

Wet mopping, single work step

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

STORAGE

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

Durability (unopened): 24 Month

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.



pH value (Concentrate): 6–7

Important ingredients:

Linseed oil, Polymers, Waxes, Surfactants

Recommended dosage:



Protective treatment

Undiluted



Wipe and care

1l in 10l

METHODS
finder

