



Product data sheet Calexan

V 02 / 13.06.2016



Wetrok Calexan

Basic sanitary cleaner



Recommended dosage (in cold water):



Maintenance cleaning

0.1–0.5 l in 10 l



Basic cleaning

1–3 l in 10 l



Foaming by hand

Min. 2 l in 10 l



Removing cement residue

Undiluted

Benefits:

Efficiently removes limescale
Can also be used as maintenance cleaner
Also suitable for removing cement residue
Can be foamed by hand

Application:

For descaling and cleaning washable and acid-resistant surfaces (sanitary porcelain, fittings, ceramic tiles, bathrooms, showers, washrooms and WCs, etc.)

Please note:


Wetrok Calexan is not suitable for acid-sensitive surfaces (limestone, marble, clinker brick, aluminium, etc.)

Moisten non-acid-resistant grout material thoroughly with water before use. The exterior of the sanitary fitting must not be warm when cleaning.

Properties:

highly acidic
lightly perfumed
high-lather
dyed red

pH value of concentrate:



Important ingredients:

Surfactants, acids, fragrance, colouring

Storage / shelf life:

Store in original container in a cool, well-ventilated place.
Protect from frost. Keep container closed when not in use.
Do not store in metal containers that may rust.
Shelf life (unopened): 24 months.

Recommended application methods:

Wet wiping (by hand)

Moisten the cleaning cloth with cleaning solution and then wring it out. Wipe the surface down with the folded wet cloth. Leave the cleaning solution to take effect. Use another cloth to pick up the dirty water. Rinse the cleaned surface with clear, cold water and wipe dry as needed.

Damp wiping (with foam)

Apply the cleaning foam in an "X" form on a folded cloth, then damp wipe the surface (using the fold technique). Rinse the cleaned surface with clear, cold water and wipe dry as needed.