



Product data sheet Ergo 2 DV-HR

V 02 / 13.07.2016

wetrok[®]

Minatol Ergo 2 DV-HR

Floor maintenance cleaner



Recommended dosage (in cold water):



Maintenance cleaning
0.1 l – 0.3 l / 10 l

Benefits:

Highly versatile all-purpose cleaner.
Removes all types of soiling.
Suitable for the food and pharma sectors.

Application:

For maintenance cleaning of water-resistant floor coverings and surfaces (PVC, natural and cast stone, clinker, asphalt, linoleum, natural rubber, etc.).


Please note:

Using a high dosage or longer application time, Ergo 2 DV-HR can dissolve or damage paintwork, varnishes and acrylic surfaces.
Use with care on anodized aluminium.

Properties:

Slightly alkaline
Contains no fragrance or colouring
Contains no vegetable stearins
Low lather

pH value of concentrate:



Important ingredients:

Chelating agent, soap, surfactants, preservatives

Storage/shelf life:

Store in original container in a cool, well-ventilated place.
Protect from frost. Keep container closed when not in use.
Shelf life (unopened): 24 months.

Recommended application methods:

Damp wiping (by hand)

Soak your cloth with cleaning solution and wring it out well.
Wipe the entire surface with the damp cloth.

Wet mopping (by hand)

Dust mop or dry vacuum the floor surface to remove dust. Soak mop with cleaning solution, wring out well and wet mop floor covering.

Scrub drying

Fill up the fresh water tank with the cleaning solution. Remove any loose dirt, and dust mop or dry vacuum the floor. Scrub dry the floor covering thoroughly with a scrubber-drier and suitable pad or brush.