




Product data sheet Reshine

V 02 / 06.07.2016



Wetrok Reshine

Floor maintenance cleaner



Recommended dosage (in cold water):



Maintenance cleaning
0.1 l – 0.2 l / 10 l



Intermediate cleaning
0.2 l – 0.5 l / 10 l



Removal of adhesive agents
1.0 l / 10 l

Benefits:

Very high-performance, multi-application maintenance cleaner. Strong and fast sponge cleaner, producing no streaks and maintaining the shine of the floor.

Application:

For maintenance cleaning of washable and alkali-resistant surfaces and floor coverings (PVC, natural and cast stone, clinker, asphalt, linoleum, natural rubber, etc.).

Please note:

Wetrok Reshine reduces microcracks and ensures a uniform appearance.

Properties:

Low lather
Slightly alkaline
Lightly perfumed

pH value of concentrate:



Important ingredients:

Surfactants, soap, solvents, chelating agent, fragrance, preservatives

Storage/shelf life:

Store in original container in a cool, well-ventilated place. Protect from frost. Keep container closed when not in use. Shelf life (unopened): 24 months.

Recommended application methods:

Wet mopping (by hand)

Dust mop or dry vacuum the floor surface to remove dust. Soak mop with cleaning solution, wring out well and wet mop floor covering.

Scrub drying

Fill up the fresh water tank with the cleaning solution. Remove any loose dirt, and dust mop or dry vacuum the floor. Scrub dry the floor covering thoroughly with a scrubber-drier and suitable pad or brush.

Removal of adhesive agents (handball resin) on sports floor coverings

First check playing field markings for chemical compatibility. Remove any loose dirt, and dust mop the floor. Apply a 10% solution of Reshine and leave to act for 15 minutes. Do not allow to dry out! Wet scrub the entire floor with a scrubber-drier with water, and then vacuum up the water (rinse).