




# Product data sheet Stoner

V 02 / 13.07.2016

# Wetrok Stoner

## Coating



### Recommended dosage (in cold water):



**Maintenance cleaning**  
0.3 l / 10 l



**Spray cleaning**  
3 l – 5 l / 10 l



**Protective treatment**  
Undiluted

### Benefits:

The stone specialist among the protective treatments. Specially developed for slightly porous natural and cast stone floor coverings.

### Application:

For treating hard and elastic floor coverings (PVC, linoleum, natural and cast stone, etc.).

### Please note:

Shake well before use!

Not suitable for water- and damp-sensitive floor coverings, for outdoor areas or wet zones.

Treat porous floor coverings with Wetrok Porosol before use.

### Properties:


Polymer/wax-based

High-shine

Water vapour diffusion guaranteed

Forms a polishable, water-resistant protective film

### pH value of concentrate:



### Important ingredients:

Polymers, wax, alkali-soluble resins, solvents, surfactants, preservatives

### Storage/shelf life:

Store in original container in a cool, well-ventilated place. Protect from frost. Keep container closed when not in use. Shelf life (unopened): 24 months.

### Recommended application methods:

#### Spray cleaning (using cleaner machine)

Remove any loose dirt, and dust mop or dry vacuum the floor. Spray on cleaning solution and work it in immediately with a single-brush machine and red pad. Reverse or replace dirty pads when worn out.

#### Protective treatment

The floor must be free of any earlier treatment and completely dry (<3% residual moisture). Dust mop or dry vacuum the floor covering. Apply the protective coating in sections in 2 to 3 thin coatings. Allow at least 60 min. drying time between coatings. If required, polish with soft pad once fully dry (after 2 to 3 days).